




proposal



TOP-LINK

Notes:

- 1 Dimensions shall be interpreted per ASME Y14.5M.
- 2 Mechanical performance(See the table 1)
- 3 Electrical performance
Resistance: 30mOhm Max.
Current rating: 3.0A
- 4 RoHS compliant.

Table 1 Mechanical performance

Max working height	7.00mm	80gf min <2.1>
Min working height	6.50mm	200gf Max
Durability	10000cycle	

Item	Part name	Q'ty/Ed	Material	Finish
1	Body	1	Leaded Brass	Au 0.4um plating Ni 1.4um
2	Plunger	1	Leaded Brass	Au 0.4um plating Ni 1.4um
3	Spring	1	Stainless steel wire	_____
4				
5				

Top-Link Electronics Ltd.	Type	Customer drawing	Unit	mm	Weight	
TOLERANCES UNLESS OTHER SPECIFIED	DWN:	Cai wonlu	APVD:			
0.0 = ±0.15	CHK:		REL:			
0.00 = ±0.10	Name	POGO PIN				
0.000 = ±0.005	Scale	1:1	Size	A4	DWG No.	C-20101011283
Angle: ±1°					Page	1/1
SURF. TEXTURE: REMOVE BURRS.					Rev.	2
BREAK SHARP EDGES R0.05 MAX.IDO NOT SCALE PRINT.						

20101011283	PART NUMBER
-------------	-------------

A

B

C

D