



Item	Part name	Q'ty/Ea'	Material	Finish
1	Body	1	Leaded Brass	Au plating over Ni
2	Plunger	1	Leaded Brass	Au plating over Ni
3	Spring	1	Stainless steel wire	_____
4				
5				

Table 1 Mechanical performance		
Max working height	5.50mm	80gf min <2.1>
Min working height	5.00mm	200gf Max
Durability	10000cycle	

- 1 Dimensions shall be interpreted per ASME Y14.5M.
- 2 Mechanical performance(See the table 1)
- 3 The force is the average of forces obtained when plunger goes downwards and upwards.
- 4 <2.2> Warning: Working height are not permitted to be less than 5.00mm working height.
- 5 Electrical performance
- 6 Resistance: 30mOhm Max.
- 7 Current rating: 2.0A
- 8 RoHS compliant.

TOP LINK

DIST  
---  
---

	NEW	2011/08/13
Rev.	Revision record.	Date.

Top-Link Electronics Ltd.		Type	Customer drawing	Unit	mm		Weight	
TOLERANCES UNLESS OTHER SPECIFIED		DWN:	APVD:		<div>Top-Link Electronics</div> <div>Top-Link Electronics Ltd</div>			
0.0 = ± 0.15		Qin zuozhong						
0.00 = ± 0.10		REL:						
0.000 = ± 0.005								
SURF. TEXTURE: REMOVE BURRS. BREAK SHARP EDGES R0.05 MAX/DO NOT SCALE PRINT.								
Angle: ±1°		Name POGO PIN						
Scale	1:1	Size	A4	DWG No.	C-101519		Page 1/1	Rev. 1

Top-Link Electronics Ltd.